



## SINIDEX HANDED STAY

Cotswold's Sinidex stays offer improved security and weather sealing through the use of a Nylon reduced friction end cap. These stays have been designed to offer smooth closure and higher performance for window applications of all sizes.

- Available in 6, 8, 10, 12", 16", 20" and 24" top hung and 8", 12" and 16" for side hung applications.
- Manufactured in the United Kingdom using high-grade Austenitic and Ferretic stainless steel.
- The stays have been proven to a lifetime 30,000 cycle guarantee

### RECOMMENDED MAXIMUM WINDOW WEIGHTS & SIZES

PRODUCT	SIZE INS	SIZE MM	APPLICATION	WINDOW SIZE APPROX WIDTH MM	WINDOW SIZE APPROX HEIGHT MM	WINDOW WEIGHT APPROX	STACK HEIGHT MM	OPENING ANGLE
HS100 6"	6	152	TOP HUNG	1200	300	10	13/14 & 16/17	62
HS100 8"	8	210	TOP HUNG	1200	300	10	13/14 & 16/17	62
HS100 8"	8	210	SIDE HUNG	400	1200	18	13/14 & 16/17	62
HS90 10"	10	260	TOP HUNG	1200	450	16	13/14 & 16/17	90
HS90 12"	12	304	TOP HUNG	1200	600	21	13/14 & 16/17	86
HS90 12"	12	304	SIDE HUNG	600	1200	24	13/14 & 16/17	86
HS90 16"	16	406	TOP HUNG	1200	750	22	13/14 & 16/17	83
HS90 16"	16	406	SIDE HUNG	700	1300	26	13/14 & 16/17	83
HS100 20"	20	511	TOP HUNG	1200	900	24	13/14 & 16/17	42
HS100 24"	24.3	616.4	TOP HUNG	1200	1500	50	13/14 & 16/17	38
HS 201	12	311	TOP/SIDE HUNG	650	1250	20	13/14 & 16/17	60
HS 216	16	406	TOP/SIDE HUNG	700	1300	28	13/14 & 16/17	52

IT IS THE RESPONSIBILITY OF THE WINDOW MANUFACTURER TO ENSURE THAT THE FINISHED WINDOW MEET ANY REQUIRED SAFETY AND PERFORMANCE SPECIFICATIONS

**Building Profiles Limited**  
 Timothy's Bridge Road  
 Stratford-upon-Avon  
 Warwickshire CV37 9NQ  
**T:** 01789 414044  
**F:** 01789 415273