



RESTRICTOR STAYS

HSR = HANDED, TSR = SECURITY HANDED

Cotswolds restrictor stays employ a simple built in child resistant catch, which limits the opening. Opening the window fully is a quick and easy one-handed operation for an adult.

- The child resistant catch limits the opening to 100mm maximum when restricted.
- Tested to BS6375 Part 2 1987 to withstand a force of 600N when opened to its restricted position.
- Either as a single for side hung or as a pair for top hung.
- Built in quick release levers allow windows to be fully opened for easy cleaning conforming to BS8213 Part 1 1991.
- The restrictor catch automatically resets when the window is closed.
- Available in 12" / 16" / 20" / 24" top hung and 12" / 16" side hung.
- Cost effective alternative to additional restrictor stays and as simple to fit as our standard FS range.
- Widely used by many social housing specifiers and fabricators.
- Suitable for BS7415 kite marked windows and all local authority.
- Manufactured in the United Kingdom using high-grade Austenitic and Ferretic stainless steel.

RECOMMENDED MAXIMUM WINDOW WEIGHTS AND SIZES

PRODUCT TOP HUNG	SIZE INS	SIZE MM	WINDOW SIZE APPROX WIDTH	WINDOW SIZE APPROX HEIGHT	WINDOW WEIGHT APPROX	STACK HEIGHT MM	RESTRICTED ANGLE	OPENING ANGLE
TSR201	12	311	1200	600	20	13/14 & 16/17	11	59
HSR201	12	311	1200	600	20	13/14 & 16/17	11	59
TSR216	16	406	1200	750	24	13/14 & 16/17	10	48
HSR216	16	406	1200	750	24	13/14 & 16/17	10	48
TSR20	20	508	1200	900	24	13/14 & 16/17	8.5	45
HSR20	20	508	1200	900	24	13/14 & 16/17	8.5	45
TSR24	24	609	1200	1200	32	13/14 & 16/17	7.6	45
HSR24	24	609	1200	1200	50	13/14 & 16/17	7.6	45
TSR201 L/R	12	311	650	1250	20	13/14 & 16/17	11	59
HSR201 L/R	12	311	650	1250	20	13/14 & 16/17	11	59
TSR216 L/R	16	406	700	1300	24	13/14 & 16/17	10	48
HSR216 L/R	16	406	700	1300	24	13/14 & 16/17	10	48

IT IS THE RESPONSIBILITY OF THE WINDOW MANUFACTURER TO ENSURE THAT THE FINISHED WINDOW MEET ANY REQUIRED SAFETY AND PERFORMANCE SPECIFICATIONS