


**PLEASE CHECK LOUVRE DIMENSIONS and ORIENTATION PRIOR TO ORDER**



Type **G30I Ducogriille**

Application: **Recess fit, flanged frame**

Blade: **Z Profile P1 Insect pierced**



**Specification:**

All profiles are aluminium extrusions manufactured to BVQI Certificate No.57832, A1 Mg Si 0.05, 1.50mm profile thickness.

**Frame Profile:**

Unequal leg outer frame to suit "recess fit" applications

**Blade:**

High security 'chevron form' interlocking aluminium extrusions

Blade Pitch: 37.5mm

**Insect Meshing:**

Integrated insect screen within punched louvre blades

Punched blade at "C"



**Water Repellent Efficiency:**

See pp46-48, Duco Architectural Grilles brochure

**Indicative airflow:**

Airflow: 2.53 L/s/dm<sup>2</sup> at 1 Pa (13 m<sup>3</sup> /h/dm<sup>2</sup> at 2 Pa)

34% physical free area (note: B/C)



Cross section of the 30Z P1 blade with 2.5mm X 21mm insect punchings at "C"

**Finish availability:**

- Mill finish
- Polyester Powder Coating
  - Standard RAL. (40-60 um)
    - MATT 30%(+/- 5%)
    - SATIN 60%(+/- 5%)
    - GLOSS 80%(+/-5%)
  - Premium RAL.
- Anodised, SAA15  Anodised, SAA25

Manufacturing tolerance = +/- 5mm on supplied dimensions



**Building Profiles Ltd**

Timothy's Bridge Road  
Stratford upon Avon  
Warwickshire, CV37 9NQ  
Tel: 01789 414044  
Fax: 01789 415273  
email: info@buildingprofiles.co.uk  
www.buildingprofiles.co.uk

\* Note: A set of four fixing lugs can be supplied on request for rear fixing (within the reveal). A 5mm deduction should be made on stated dimensions if fixing lugs are required